

Attenuation	R1	R2(a)	R2(b)	Atten (actual)	Input impedanc e	Atten error (dB)
0	0	13000	(no res)	0	10182.3	0
-2	2000	9100	(no res)	-2.02	9623.3	-0.02
-4	3900	7500	(no res)	-4.1	10367.5	-0.1
-6	5100	5600	(no res)	-6.1	10103.6	-0.1
-8	6200	6200	16000	-8.03	10280.5	-0.03
-10	6800	4300	16000	-9.97	9961.2	0.03
-12	7500	2700	(no res)	-11.9	10053.3	0.1
-14	8200	2700	10000	-14.03	10234	-0.03
-16	8200	1600	(no res)	-15.99	9747.3	0.01
-18	8200	1200	(no res)	-18.07	9370.1	-0.07
-20	9090	1500	3300	-20.01	10099.1	-0.01
-22	9090	1200	2400	-21.98	9876.6	0.02
-24	9090	620	(no res)	-24	9701.9	0
-26	9090	560	3600	-26	9569.7	0
-28	10000	680	1100	-27.96	10416.5	0.04
-30	10000	330	(no res)	-29.97	10327.7	0.03
-32	10000	330	1200	-32.01	10257.4	-0.01
-34	10000	360	470	-34.03	10203	-0.03
-36	10000	160	(no res)	-36.08	10159.5	-0.08
-38	10000	240	270	-38.05	10126.7	-0.05
-40	10000	100	(no res)	-40.1	10099.8	-0.1
-42	10000	120	240	-42.02	10079.9	-0.02
-44	10000	110	150	-44.02	10063.4	-0.02
-46	10000	51	(no res)	-45.9	10050.9	0.1
-48	10000	47	270	-47.99	10040	0.01
-50	10000	36	270	-49.99	10031.7	0.01
-52	10000	30	150	-52.07	10025	-0.07
-54	10000	20	(no res)	-54	10020	0
-56	10000	16	(no res)	-55.93	10016	0.07
-58	10000	13	430	-57.99	10012.6	0.01
-60	10000	10	(no res)	-60.01	10010	-0.01
-62	10000	8.2	270	-61.99	10008	0.01
-64	10000	8.2	27	-64.03	10006.3	-0.03